

# **STS-1-VBB Sensor Replacement Program**

**Tom VanZandt, Metrozet, LLC**

**Barbara Romanowicz, Bill Karavas, and John Friday, Berkeley Seismological Laboratory**

**Erhard Wielandt, University of Stuttgart (retired)**

**In collaboration with:**

**Joe Steim, Quanterra, Inc.**

**Bob Hutt, ASL**

**March, 2011**

**metrozet**

## **VBB Sensor Design and Status**

Non-Galperin architecture (separate H and V sensor designs)

Very similar to original STS-1

Factory-leveled sensor elements: no field leveling required (ala STS-2)

Triaxial package with "warpless" design and kinematic sensor mounting

External electronics (slightly modified version of STS1-E300)

Modern, "volume-manufactured" design with adequate production throughput

High-level of modularity:

Sensors, electronics, and cabling can be swapped out during field maintenance

Individual components can be replaced by Metrozet

Rather than returning entire system for repair



*2008-2009 development testing at UC Berkeley (BKS) indicated sensor performance similar to BKS STS-1 sensors*

**2010 Has focused on development of VBB commercial prototypes:**

**12 triaxial packages**

**12 sets of modified electronics,**

**15 triaxial sets of sensor elements**



## **VBB Commercial Prototype Testing**

### *Initial functional test at Byerly Vault (BKS)*

Began in April, 2010

8 systems evaluated to date

### *Longer-term performance testing at HRV*

May, 2010 through January, 2011

6 triaxial packages and 7 triaxial sensor sets evaluated to date

2 to 3 month measurement period

Cross-comparison with HRV GSN STS-1 sensors in vault

### *Partner/Customer evaluation at ASL: September 2010-February 2011*

2 complete systems installed: one in cross-tunnel and one in outer vault

Cross-tunnel system installed on granite slab with (unpacked) STS-1H pair


Sand-packed STS-1Z is on tunnel floor, adjacent to slab

***One complete system (so-called "MET22") is now retained at ASL on semi-permanent basis***

***Another system (so-called "MET06") is now retained at BKS on semi-permanent basis***

## Data from ASL

### Vertical Sensor: 2 Days after "final" installation of sensors in cross-tunnel



White: Metrozet Z Prototype in Triaxial Package


Red: ASL Reference STS-1Z Sand-Packed

Day 274 data; 30 second LP Filtered; Scalar-Deconvolved Only;  
Not Deconvolved of Poles/Zeros

# Power Spectral Density (PSD) Analysis


ASL day 274 data: 500 Second Pieces, 80 averages, 0% overlap; equivalent sensor assumption

Signal, Incoherent Noise and NLNM PSD



Same data: 2000 Second Pieces, 20 averages, % overlap; equivalent sensor assumption

Signal, Incoherent Noise and NLNM PSD



## **Japan M9.0 Event Captured faithfully on systems installed at both UC Berkeley (BKS) and at ASL**

For data or details, contact:

### ***ASL Data:***

Bob Hutt (bhutt@usgs.gov)

Joe Steim (steim@quanterra.com)

### ***BKS Data:***

Tom VanZandt (tom.vanzandt@metrozet.com)

Rob Porritt (rob@seismo.berkeley.edu)

## **Product Schedule**

Late 2010: Address remaining technical issues and finalize commercial prototype sensors

Mid-2011: Release (sell) select prototype systems for customer evaluation

Late 2011: Expect to ship commercial systems in volume